

HS-2510W/2512W



Specification	HS-2510W	HS-2512W
Processor	Intel Celeron J1900 Quad Core CPU, 2GHz/2.42GHz (Burst)	
System Memory	DDR3L 1333MHz, SO-DIMM x 1, max. 8GB	
Storage Device	SATA Storage x 2 or eMMC x 1	
Display	9.7" 1024 x 768 LCD panel	12" 1024 x 768 LCD panel
Touch	True-flat PCAP touch with multi-touch support (IP65 on front panel)	
Built-in Printer	3" thermal printer with auto cutter, 200mm/sec print speed	
Power Supply	12V DC power adaptor, 100W	12V DC power adaptor, 100W
OS Support	Windows 7/POSReady 7/Window Embedded 8.1 Industry/Linux per request/Windows 10 IoT	

Connectivity

LAN Port	10/100/1000Mb x 1	
Serial Port	DB9 x 2 + RJ45 x 1 with 5V/12V support on COM1/COM2/COM3, RJ45 to DB9 cable optional	
Parallel Port	Yes	
Standard USB Port	4, 1 x USB 3.0/2.0 + 3 x USB 2.0	
PS/2 Port	Yes	
VGA Port	D-SUB, 15 pins, with 12V support for Posiflex monitor	
Audio Port	Line out	
Mini-PCIe slot	Yes, for half size card	
CR Port	1, control 2 CR	

Physical Dimension

Dimension [W x D x H in mm]	224.5 x 185 x 387	297 x 187 x 402
Weight [N.W. in Kg]	4.2	5.3

Environment

Operation Condition	0°C - 40°C, 20%RH - 90%RH (Equipped with HDD); 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)	
Storage Condition	-20°C - 70°C, 10%RH - 90%RH	

Options

SSD	2.5" or 1" SATA SSD	
eMMC	16GB/32GB module	
MSR	Integrated 3 track module (HID/VCOM Selectable)	
Smartcard Reader	Integrated	
RFID	Integrated, support MIFARE Ultralight and Classic 1K card (HID/VCOM Selectable)	
Finger Print Sensor	Integrated	
LM-6507	7" 800 x 480 rear-mount 2nd display for HS Series (USB interface)	
PD-6507	7" color graphical line display, rear-mount (USB interface)	
PD-2607UE	2 x 20 VFD, rear-mount, USB with Virtual COM support	
PD-340UE	2 x 20 LCD, rear-mount, USB with Virtual COM support	
WIFI	Internal mini-PCIe WIFI module with PIFA antenna	

* The product information and specifications are subject to change without prior notice.
* Please refer to the web site for more attachment options.

Certifications



Design and Manufacturing in Taiwan by Posiflex Technology Inc.
The product information and specifications are subject to change without prior notice.

2016Q1



POSIFLEX TECHNOLOGY INC.
No. 6, Wuquan Rd., Wugu Dist., New Taipei City 24886, Taiwan
Tel : +886-2-2299-1599 E-mail : sales@posiflex.com.tw
Fax : +886-2-2299-1819 www.posiflex.com

Authorized Distributor / Reseller

Taking Space Saving To Extreme



HS-2510W/2512W

Space Saving All-in-one POS Terminal



Overview

The HS-2500 Series is the solution for the counter space problem. It takes the all-in-one concept to the extreme! The compact all-in-one design of HS-2500 Series frees more room for counter space, so that the store owner can display and promote more merchandizes to maximize sales opportunities.



Compact

The compact footprint of HS-2500 Series makes itself adaptable to a wide range of counter styles and allows every inch of the work space usage to be optimized, thus creating maximum profit return for the store owners. This is what space saving is all about.

All-in-one

As an "All-in-one" solution, HS-2500 Series touch-screen terminal integrates some of the most widely used peripherals in daily POS operation, such as 3" thermal printer, MSR, smart card reader, finger print sensor and 2nd customer display, and has the features and functionality to cater for applications in retail, hospitality, health care, banking and more, while offering uncompromising performance.



Aesthetics

Dressed from head to toe in timeless black or white color, the only trend that never goes out of style, and with stylish touches added throughout, HS-2500 Series is not just a piece of machinery, it is an elegantly crafted piece of art that looks right at home in any store decoration.



Easy paper roll access



Built-in 3" thermal printer



Optional built-in MSR, smartcard reader, finger print sensor and RFID reader