

SERVICE CONDITIONS

SERVICE CONDITIONS	Required torque O (Nm) ... : 2500	Stem diam. (mm) : 0.00
	Required torque C (Nm) ... : 2500	VALVE Lead (mm) : 0.00
	Number of turns in output .. : 0.25	Lift (mm) : 0.00
Closing direction	: Clockwise	
Customer specifications	:	
Observation	:	

ACTUATOR

Actuator	: SQ250	Actuator's speed (Rpm)	: 0.21
----------------	---------	------------------------------	--------

MECHANICAL SPECIFICATIONS

Protection	: _NotExplosionProof IP67	Output flange	: F16
Box type	: FPI	Output form	: N/A
Class	: A	Machining type	: Plain socket
Output speed (RPM)	: 0.21	Manual command	: Declutchable Ø 300 mm
Operating time (s)	: 70	Paint	: BCPS-C3-01
Max torque (Nm)	: 2500	Painting process	: Intermediate Corrosi
Torque set O (Nm)	: 2500	Color	: RAL 5002 MARINE BLUE
Torque set C (Nm)	: 2500		
Temperature	: Standard -20°C to 70°C		

MOTOR SPECIFICATIONS

Motor	: Electric 3Ph 400V 50Hz	Motor duty (%)	: S4 - 30
Power (kW)	: 0.100	Nominal intensity (A) :	0.60
		Starting current (A)	: 1.20

ELECTRICAL SPECIFICATIONS

Control type	: POSIGAM+	Wiring diagram	: S62500002
Options (incl.)	: VS3 - Pot 1 x 1KΩ STD		
End of travel limit switches ... :	Opening : 2 & Closing : 2 - Type : SPDT		
Torque limit switches qty	Opening : 1 & Closing : 1 - Type : SPDT		
Customer's connection	: Plug plastic 3xM20 ISO		
Heater	: 400 V 25 W		

PARTICULAR SPECIFICATIONS

Quality level	: Q3	Quality plan	:	Dimensional drawing ... :	Z216100 Ver. C
Electronic card's configure:	Standard			Orientations :	