



MODEL NO.

81-20516-A3

PRODUCT LINE

GO Switch Leverless Limit Switches

SPECIFICATIONS

Model GO Switch Model 81- 1-1/2" square x 4 7/8".
 Subtract 1/2" from length for side conduit

Contact Form DPDT (Form CC) 10A@120VAC /

Sensing Range Approx. 6mm (1/4") end sensing

Outlet Position Bottom of enclosure - 1/2" NPT

Enclosure Material Brass - coated with flat black lacquer

Approvals CSA/FM Explosion Proof CI I, Div 2; Grps A-D; CI II, Div 2, Grps E-G; CI III (lead seal req'd within 18")

Wiring Options PVC Lead Wires - 18 gauge - 1829mm (6ft)

Operating Temps* -40 °C to 105 °C

PVC & Teflon Leads

| | |
|----------------------------------|---------------------------|
| N/C1 - Red | N/C2 - Red/White Stripe |
| N/O1 - Blue | N/O2 - Blue/White Stripe |
| COM1 - Black | COM2 - Black/White Stripe |
| (CSA approvals only) GND - Green | |

Termination A & F

S-K025 Rev. 4, 0406-5M
L-L098



Current as of Apr 18, 2016 - subject to change without notice.

TOPWORX

TopWorx (502) 969-8000 ph.
 3300 Fern Valley Rd. (502) 969-5911 fax
 Louisville, KY 40213 www.topworx.com