



Parker Legris: Nickel-Plated Brass Accessories

aerospace
climate control
electromechanical
filtration
fluid & gas handling
hydraulics
pneumatics
process control
sealing & shielding



ENGINEERING YOUR SUCCESS.



This document presents our enhanced range of nickel-plated brass accessories, including new configurations.

Find the complete Parker Legris offer in our 2013 general Catalogue.

Together, we can connect you to the best in technology.
Better than ever before.

A Complete Range of Adaptors

Nickel-Plated Brass Adaptors

0912
BSPP/Metric
Page 5



0921
Metric
Page 5



0913
BSPT/BSPP
Page 5



0922
Metric
Page 5



0914
BSPT
Page 5



0910
BSPP
Page 6



0911
BSPT/BSPP
Page 6



0915
BSPP/Metric
Page 6



0923
Metric
Page 6



0916
BSPT/BSPP
Page 6



0924
Metric
Page 7



0917
BSPT/BSPP
Page 7



0927
BSPT
Page 7



0928
BSPT/BSPP
Page 7



0932
BSPT/BSPP
Page 7



0908
BSPP
Page 8



0909
BSPT/BSPP
Page 8



0903
BSPP
Page 8



0904
BSPT/BSPP
Page 8



0905
BSPP/Metric
Page 8



0933
BSPT/BSPP
Page 9



0906
BSPP/Metric
Page 9



0907
BSPP
Page 9



0920
BSPP/Metric
Page 9



New

New

0900
BSPT
Page 10



0901
BSPP/Metric
Page 10



0192
BSPT/BSPP
Page 10



0902
BSPP/Metric
Page 10



0191
BSPP
Page 11



0931
BSPP
Page 11



0934
BSPT
Page 11



0935
BSPP
Page 12



New

New

Nickel-Plated Brass Hollow Hex Plugs

0936
BSPT
Page 13



New

0919
BSPP/Metric
Page 13



Adaptors and Plugs

Parker Legris offers a **wide range of adaptors** compatible with the various Parker Legris fitting systems. This range of products provides the user with a **complete solution** covering numerous applications, both in non-corrosive and corrosive environments.

Product Advantages

- Large Range & Flexibility**
 - A complete offer, including adaptors and plugs
 - Surface treatment for increased corrosion resistance: nickel-plated brass
 - BSPP, BSPT and metric threads
- Performance**
 - Robust design
 - Forged shapes for mechanical strength



Technical Characteristics

Products	Adaptors and Plugs
Working Pressure	60 bar
Working Temperature	-10°C to +80°C

Component Material



New configurations are now available.



0933



0934



0935



0936

Nickel-Plated Brass Adaptors

0912 Equal Stud Elbow, Female BSPP and Metric Thread

	Nickel-plated brass 	C		E	G	J	L	kg
		M5x0.8	0912 00 19	4	8	9	11	0.006
		G1/8	0912 00 10	8	13	10	18.5	0.015
		G1/4	0912 00 13	11	17	12	22.5	0.028
		G3/8	0912 00 17	11.5	21	15	25.5	0.043
		G1/2	0912 00 21	14	26	19	30	0.073
		G3/4	0912 00 27	16.5	32	22	35.5	0.143
		G1	0912 00 34	18	38.5	28	40.5	0.166

0921 Equal Stud Elbow, Male/Female, Metric Thread

	Nickel-plated brass 	C		E	G	H	J	L	kg
		M5x0.8	0921 00 19	4	8	11	9	11	0.006

0913 Equal Stud Elbow, Male BSPT/ Female BSPP Thread

	Nickel-plated brass 	C1	C2		E	G	H	J	L	kg
		R1/8	G1/8	0913 00 10	8	13	17	10	18.5	0.012
		R1/4	G1/4	0913 00 13	11	17	22.5	12	22.5	0.026
		R3/8	G3/8	0913 00 17	11.5	21	25.5	15	25.5	0.038
		R1/2	G1/2	0913 00 21	14	26	30	19	30	0.064
		R3/4	G3/4	0913 00 27	16.5	32	34.5	22	35.5	0.098
		R1	G1	0913 00 34	18	38.5	40.5	28	40.5	0.146

0922 Equal Stud Elbow, Male Metric Thread




	Nickel-plated brass 	C		H	J	L	kg
		M5x0.8	0922 00 19	11	9	11	0.010

0914 Equal Stud Elbow, Male BSPT Thread




	Nickel-plated brass 	C		H	J	L	kg
		R1/8	0914 00 10	17	10	17	0.012
		R1/4	0914 00 13	22.5	12	22.5	0.027
		R3/8	0914 00 17	25.5	15	25.5	0.035
		R1/2	0914 00 21	30	19	30	0.056
		R3/4	0914 00 27	34.5	22	34.5	0.104
		R1	0914 00 34	40.5	28	40.5	0.156

Nickel-Plated Brass Adaptors




0910 Equal Y, Female BSPP Thread

	<p>Nickel-plated brass</p> 	C		E	F	H	kg
		G1/8	0910 00 10	8	13	12	0.018
		G1/4	0910 00 13	11	17	14	0.033
		G3/8	0910 00 17	11.5	20	16	0.045
		G1/2	0910 00 21	14	25	19	0.083




0911 Equal Y, Male BSPT/Female BSPP Thread

	<p>Nickel-plated brass</p> 	C1	C2		E	F	H	kg
		R1/8	G1/8	0911 00 10	8	13	12	0.022
		R1/4	G1/4	0911 00 13	11	17	14	0.038
		R3/8	G3/8	0911 00 17	11.5	20	16	0.050
		R1/2	G1/2	0911 00 21	14	25	19	0.103




0915 Equal Tee, Female BSPP and Metric Thread

	<p>Nickel-plated brass</p> 	C		E	G	H	J	L/2	kg
		M5x0.8	0915 00 19	4	8	11	9	11	0.010
		G1/8	0915 00 10	8	13	18.5	10	18.5	0.021
		G1/4	0915 00 13	11	17	22.5	12	22.5	0.042
		G3/8	0915 00 17	11.5	21	25.5	15	25.5	0.062
		G1/2	0915 00 21	14	26	30	19	30	0.099
		G3/4	0915 00 27	16.5	32	35.5	22	35.5	0.143
		G1	0915 00 34	18	38.5	40	28	40	0.244

0923 Equal Stud Branch Tee, Female/Male Metric Thread




	<p>Nickel-plated brass</p> 	C		E	G	H	J	L/2	kg
		M5x0.8	0923 00 19	4	8	11	9	11	0.009

0916 Equal Stud Branch Tee, Male BSPT/Female BSPP Thread




	<p>Nickel-plated brass</p> 	C1	C2		E	G	H	J	L/2	kg
		R1/8	G1/8	0916 00 10	8	13	17	10	18.5	0.019
		R1/4	G1/4	0916 00 13	11	17	23.5	13	22.5	0.038
		R3/8	G3/8	0916 00 17	11.5	21	25.5	15	25.5	0.076
		R1/2	G1/2	0916 00 21	14	26	30	19	30	0.091
		R3/4	G3/4	0916 00 27	16.5	32	34.5	22	35.5	0.140
		R1	G1	0916 00 34	18	38.5	40.5	28	40.5	0.237

Nickel-Plated Brass Adaptors




0924 Equal Stud Run Tee, Female/Male Metric Thread

	Nickel-plated brass 	C1	C2		E	G	H	H1	J	L	kg
		M5x0.8	M5x0.8	0924 00 19	4	8	11	11	9	11	0.009




0917 Equal Stud Run Tee, Male BSPT/Female BSPP Thread

	Nickel-plated brass 	C1	C2		E	G	H	H1	J	L	kg
		R1/8	G1/8	0917 00 10	8	13	17	18.5	10	18.5	0.025
		R1/4	G1/4	0917 00 13	11	17	22.5	22.5	12	22.5	0.038
		R3/8	G3/8	0917 00 17	11.5	21	25.5	25.5	15	25.5	0.058
		R1/2	G1/2	0917 00 21	14	26	30	30	19	30	0.090
		R3/4	G3/4	0917 00 27	16.5	32	34.5	35.5	22	35.5	0.177
		R1	G1	0917 00 34	18	38.5	40.5	40.5	28	40.5	0.219




0927 Equal Tee, Male BSPT Thread

	Nickel-plated brass 	C		H	J	L	kg
		R1/8	0927 00 10	17	10	34	0.018
		R1/4	0927 00 13	22.5	12	45	0.032
		R3/8	0927 00 17	25.5	15	51	0.056
		R1/2	0927 00 21	30	19	60	0.094
		R3/4	0927 00 27	34.5	22	69	0.133
		R1	0927 00 34	40.5	28	81	0.217

0928 Equal Stud Branch Tee, Male BSPT/Female BSPP Thread

	Nickel-plated brass 	C1	C2		E	H	J	L	kg
		R1/8	G1/8	0928 00 10	8	34	10	18.5	0.016
		R1/4	G1/4	0928 00 13	11	45	12	22.5	0.044
		R3/8	G3/8	0928 00 17	11.5	51	15	25.5	0.053
		R1/2	G1/2	0928 00 21	14	60	19	30	0.111
		R3/4	G3/4	0928 00 27	16.5	69	22	35.5	0.236
		R1	G1	0928 00 34	18	81	28	40.5	0.225

0932 Equal Stud Run Tee, Male BSPT/Female BSPP Thread

	Nickel-plated brass 	C1	C2		E	H	H1	J	L	kg
		R1/8	G1/8	0932 00 10	8	17	18.5	10	17	0.016
		R1/4	G1/4	0932 00 13	11	22.5	22.5	12	22.5	0.035
		R3/8	G3/8	0932 00 17	11.5	25.5	25.5	15	25.5	0.055
		R1/2	G1/2	0932 00 21	14	30	30	19	30	0.091
		R3/4	G3/4	0932 00 27	16.5	34.5	35.5	22	34.5	0.080
		R1	G1	0932 00 34	18	40.5	40.5	28	40.5	0.226

Nickel-Plated Brass Adaptors

0908 Equal Cross, Female BSPP Thread

	Nickel-plated brass 	C		E	G	H	J	kg
		G1/8	0908 00 10	8	13	21	10	0.038
		G1/4	0908 00 13	11	17	25.5	13	0.073
		G3/8	0908 00 17	11.5	21	28	17	0.107
		G1/2	0908 00 21	14	26	33.5	21	0.189

0909 Equal Cross, Male BSPT/Female BSPP Thread

	Nickel-plated brass 	C1	C2		E	G	H	J	kg
		R1/8	G1/8	0909 00 10	8	13	18.5	10	0.034
		R1/4	G1/4	0909 00 13	11	17	23.5	13	0.068
		R3/8	G3/8	0909 00 17	11.5	21	26	17	0.099
		R1/2	G1/2	0909 00 21	14	26	31	21	0.168

0903 Reducer, Male/Female BSPP Thread

	Nickel-plated brass 	C1	C2		E	F	kg
		G1/4	G1/8	0903 10 13	8	6	0.004
		G3/8	G1/4	0903 13 17	9	8	0.006
		G1/2	G3/8	0903 17 21	10	10	0.010
		G3/4	G1/2	0903 21 27	14	12	0.022
		G1	G3/4	0903 27 34	20	17	0.036

0904 Reducer, Male BSPT/Female BSPP Thread

New 	Nickel-plated brass 	C1	C2		F	L	kg
		R1/4	G1/8	0904 10 13	14	16	0.010
		R3/8	G1/8	0904 10 17	17	16.5	0.020
			G1/4	0904 13 17	17	16.5	0.015
		R1/2	G1/8	0904 10 21 *	22	19.5	0.046
			G1/4	0904 13 21	22	19.5	0.032
			G3/8	0904 17 21	22	19.5	0.025
		R3/4	G3/8	0904 17 27	27	23.5	0.057
			G1/2	0904 21 27	27	23.5	0.044
		R1	G1/2	0904 21 34 *	34	27	0.130
			G3/4	0904 27 34 *	34	27	0.770

* Additional part numbers

0905 Reducer, Male BSPP/Female BSPP and Metric Thread

	Nickel-plated brass 	C1	C2		E	F	L	kg
		G1/8	M5x0.8	0905 19 10	6	14	4.5	0.008
		G1/4	G1/8	0905 10 13	8	17	5	0.011
		G3/8	G1/8	0905 10 17	9	19	5	0.019
			G1/4	0905 13 17	9	19	5	0.013
		G1/2	G1/4	0905 13 21	10	24	5.5	0.032
			G3/8	0905 17 21	10	24	5.5	0.022
		G3/4	G3/8	0905 17 27	12	30	5.5	0.053
			G1/2	0905 21 27	12	30	5.5	0.041


Nickel-Plated Brass Adaptors

0933 Increaser, Male BSPT/Female BSPP Thread

New



Nickel-plated brass




C1	C2		E	F	L	kg
R1/8	G1/8	0933 00 10	8	14	18	0.011
	G1/4	0933 10 13	11	17	21.5	0.018
	G3/8	0933 10 17	11.5	22	22.5	0.029
R1/4	G1/4	0933 00 13	11	17	24.5	0.022
	G3/8	0933 13 17	11.5	22	25.5	0.034
	G1/2	0933 13 21	14	24	29	0.045
R3/8	G3/8	0933 17 17	11.5	22	26	0.037
	G1/2	0933 17 21	14	24	29.5	0.030
R1/2	G1/2	0933 00 21	14	26	32	0.050
	G3/4	0933 21 27	16.5	32	35	0.080

0906 Increaser, Male BSPP and Metric/Female BSPP Thread



Nickel-plated brass




C1	C2		E1	E2	F	L	kg
M5x0.8	G1/8	0906 10 19	4	8	14	10	0.009
	G1/8	0906 00 10	6	8	14	10	0.011
G1/8	G1/4	0906 10 13	6	11	17	14	0.016
	G3/8	0906 10 17	6	11.5	22	14.5	0.029
G1/4	G1/4	0906 00 13	8	11	17	14	0.020
	G3/8	0906 13 17	8	11.5	22	14.5	0.032
	G1/2	0906 13 21	8	15	27	18	0.037
G3/8	G3/8	0906 00 17	9	11.5	22	14.5	0.034
	G1/2	0906 17 21	9	14	27	18	0.038
G1/2	G1/2	0906 00 21	10	14	27	18	0.054

0907 Equal Extended Adaptor, Male/Female BSPP Thread



Nickel-plated brass




C		E	F	L	kg
G1/8	0907 00 10	6	14	16	0.015
	0907 00 10 01	6	14	36	0.029
G1/4	0907 00 13	8	17	26	0.032
	0907 00 13 01	8	17	43	0.046

0920 Bulkhead Connector, Female BSPP and Metric Thread



Nickel-plated brass



C	C1	F	F1	K _{max}	L	L1	ØT	kg	
M5x0.8	M10x1	0920 00 19	14	14	7	10.5	3.5	10.5	0.012
G1/8	M16x1.5	0920 00 10	19	22	9	14	4	16.5	0.029
G1/4	M20x1.5	0920 00 13	24	27	15	21	4	20.5	0.056
G3/8	M26x1.5	0920 00 17	30	32	14	21	5	26.5	0.095
G1/2	M28x1.5	0920 00 21	32	36	20	27	6	28.5	0.115

Nickel-Plated Brass Adaptors

0900 Equal and Unequal Adaptor, Male BSPT Thread

	Nickel-plated brass		C1	C2		F	L	kg
			R1/8	R1/8	0900 00 10	12	19.5	0.008
			R1/8	R1/4	0900 10 13	14	23.5	0.015
				R3/8	0900 10 17	17	24	0.020
			R1/4	R1/4	0900 00 13	14	27	0.017
				R3/8	0900 13 17	17	27.5	0.026
			R3/8	R1/2	0900 13 21	22	30.5	0.044
				R3/8	0900 00 17	17	28	0.026
			R1/2	R1/2	0900 00 21	22	33.5	0.044
				R3/4	0900 21 27	27	37.5	0.084
			R3/4	R3/4	0900 00 27	27	40	0.079
				R1	0900 27 34	34	43	0.144
			R1	R1	0900 00 34	34	45.5	0.153

0901 Equal and Unequal Adaptor, Male BSPP and Metric Thread

	Nickel-plated brass		C1	C2		E	E1	F	L	kg
			M5x0.8	M5x0.8	0901 00 19	4	4	8	11.5	0.002
			M5x0.8	G1/8	0901 19 10	4	6	14	14.5	0.008
				G1/8	0901 00 10	6	6	14	16.5	0.009
			G1/8	G1/4	0901 10 13	6	8	17	19	0.016
				G1/4	0901 00 13	8	8	17	21	0.019
			G1/4	G3/8	0901 13 17	8	9	19	22	0.023
				G3/8	0901 00 17	9	9	19	23	0.025
			G3/8	G1/2	0901 17 21	9	10	24	24.5	0.038
				G1/2	0901 00 21	10	10	24	25.5	0.041

0192 Equal and Unequal Straight Adaptor, Male BSPT/BSPP Thread

	Nickel-plated brass		C1	C2		E	F	L	kg
			R1/8	G1/4	0192 10 13	9.5	17	23.5	0.019
			R1/4	G1/4	0192 13 13	9.5	17	27.5	0.024
				G1/2	0192 13 21	11	27	31.5	0.068
			R3/8	G1/4	0192 17 13	9.5	17	28	0.025
				G1/2	0192 17 21	11	27	31.5	0.061
			R1/2	G1/2	0192 21 21	11	27	34	0.061

0902 Equal and Unequal Adaptor, Female BSPP and Metric Thread

	Nickel-plated brass		C1	C2		F	L	kg
			M5x0.8	M5x0.8	0902 00 19	8	11	0.003
			M5x0.8	G1/8	0902 19 10	14	13	0.009
				G1/8	0902 00 10	14	15	0.010
			G1/8	G1/4	0902 10 13	17	19.5	0.017
				G3/8	0902 10 17	22	20	0.028
			G1/4	G1/4	0902 00 13	17	22	0.019
				G3/8	0902 13 17	22	23	0.031
			G1/4	G1/2	0902 13 21	27	27	0.033
				G3/8	0902 00 17	22	24	0.034
			G3/8	G1/2	0902 17 21	27	27.5	0.037
				G1/2	0902 00 21	27	30	0.050
			G1/2	G3/4	0902 21 27	30	30	0.077
				G3/4	0902 00 27	30	32	0.080

Nickel-Plated Brass Adaptors

0191 Tailpiece Adaptor for Rubber Hose, Male BSPP Thread

ØD	ØD1	C	Nickel-plated brass	E	F	K	L	kg
4	6	G1/4	0191 04 13	9.5	17	5	22.5	0.019
	9	G1/4	0191 07 13	9.5	17	5	22.5	0.022
7	9	G1/2	0191 07 21	11	27	7	29.5	0.065
	12.2	G1/4	0191 10 13	9.5	17	5	22.5	0.020
10	12.2	G1/2	0191 10 21	11	27	7	29.5	0.061
	15.2	G1/4	0191 13 13	9.5	17	5	22.5	0.022
13	15.2	G1/2	0191 13 21	11	27	7	29.5	0.058
	16	G1/2	0191 16 21	11	27	7	36.5	0.067

0931 Tailpiece Adaptor for Rubber Hose, Male BSPP Thread

ØD	ØD1	C	Nickel-plated brass	E	F	K	L	kg
6	7	G1/8	0931 06 10	6	12	4	20	0.009
	7	G1/4	0931 06 13	8	14	5	20	0.013
7	8	G1/8	0931 07 10	6	12	4	20	0.009
	8	G1/4	0931 07 13	8	14	5	20	0.013
8	8	G3/8	0931 07 17	9	19	5	20	0.022
	9	G1/8	0931 08 10	6	12	4	20	0.009
8	9	G1/4	0931 08 13	8	14	5	20	0.014
	9	G3/8	0931 08 17	9	19	5	20	0.022
10	12	G1/4	0931 10 13	8	14	5	20	0.016
	12	G3/8	0931 10 17	9	19	5	20	0.024
15	12	G1/2	0931 10 21	10	22	6	22	0.031
	17	G3/8	0931 15 17	9	19	6	24	0.030
18	17	G1/2	0931 15 21	10	22	6	24	0.037
	20	G1/2	0931 18 21	10	22	6	24	0.039

0934 Hose Barb Adaptor, Male BSPT Thread

ØD	C	Nickel-plated brass	F	L	L1	kg
6	R1/8	0934 06 10	12	31.5	19	0.009
	R1/4	0934 06 13	14	35	19	0.014
7	R1/8	0934 07 10	12	31.5	19	0.009
	R1/4	0934 07 13	14	35	19	0.014
8	R1/8	0934 08 10	12	31.5	19	0.010
	R1/4	0934 08 13	14	35	19	0.015
9	R1/8	0934 09 10	12	31.5	19	0.012
	R1/4	0934 09 13	14	35	19	0.015
9	R3/8	0934 09 17	17	35.5	19	0.021
	R1/2	0934 09 21	22	38.5	19	0.032
10	R1/8	0934 10 10	12	32.5	20	0.010
	R1/4	0934 10 13	14	36	20	0.015
10	R3/8	0934 10 17	17	36.5	20	0.022
	R1/2	0934 10 21	22	39.5	20	0.033
12	R1/4	0934 12 13	14	36	20	0.019
	R3/8	0934 12 17	17	36.5	20	0.021
12	R1/2	0934 12 21	22	39.5	20	0.033
	R3/8	0934 14 17	17	38.5	22	0.023
14	R1/2	0934 14 21	22	41.5	22	0.036
	R3/8	0934 16 17	17	38.5	22	0.026
16	R1/2	0934 16 21	22	41.5	22	0.038
	R3/4	0934 16 27	27	45	22	0.062
17	R3/8	0934 17 17	18	40.5	24	0.030
	R1/2	0934 17 21	22	43.5	24	0.043
18	R3/8	0934 18 17	19	40.5	24	0.031
	R1/2	0934 18 21	22	43.5	24	0.043
18	R3/4	0934 18 27	27	47	24	0.062
	R3/8	0934 20 17	22	41	24	0.038
20	R1/2	0934 20 21	22	43.5	24	0.046

Nickel-Plated Brass Adaptors


0935


Hose Barb Adaptor, Female BSPP Thread

New



Nickel-plated brass



	ØD	C		E	F	L	L1	kg
6	G1/8		0935 06 10	8	12	28.5	19	0.011
7	G1/8		0935 07 10	8	12	28.5	19	0.012
	G1/4		0935 07 13	11	15	31.5	19	0.019
8	G1/4		0935 08 13	11	15	31.5	19	0.019
9	G1/4		0935 09 13	11	15	31.5	19	0.020
	G3/8		0935 09 17	11.5	19	32	19	0.025
10	G3/8		0935 10 17	11.5	19	33	20	0.025
12	G3/8		0935 12 17	11.5	19	33	20	0.027
	G1/2		0935 12 21	14	24	36	20	0.040


Nickel-Plated Brass Plugs

0936 Internal Hexagon Head Plug, Male BSPT Thread

New



Nickel-plated brass




C		F	H	H1	kg
R1/8	0936 00 10	5	8	8	0.002
R1/4	0936 00 13	6	10	7	0.007
R3/8	0936 00 17	8	11	7.5	0.013
R1/2	0936 00 21	10	13	8	0.025

0919 Internal Hexagon Head Plug, Male BSPP and Metric Thread



Nickel-plated brass



C		E	F	G	H	kg
M5x0.8	0919 00 19	4	2.5	8	7.5	0.001
G1/8	0919 00 10	6	3	15	10	0.007
G1/4	0919 00 13	8	6	18	12	0.013
G3/8	0919 00 17	9	8	21	13	0.021
G1/2	0919 00 21	10	10	25	14.5	0.036
G3/4	0919 00 27	11	30	-	17	0.050
G1	0919 00 34	13	38	-	19	0.076

Related Products

You will find all related products associated with this range of accessories in our general Catalogue and on our Internet website, www.parkerlegris.com.

LF 3600 Push-in Fittings



In order to meet your **technical and environment requirements**, Parker Legris designed this range of metal fittings (brass nickel-plated), offering **robustness, reliability** and **resistance to industrial fluids** for the most demanding environments.

Function Fittings



Parker Legris flow control regulators with polymer, nickel-plated brass or aluminium bodies, external or recessed adjustment screws offer **precise adjustment, accuracy** and **compactness** providing the solution for all applications.

Tubing

Polyamide Tubing (PA)



Tried-and-tested for industrial or vehicle applications, PA tubing guarantees **excellent durability** due to its stable long-term mechanical properties. Parker Legris' special grade of semi-rigid polyamide is manufactured according to our **Eco-Design** approach for higher performance.

Polyurethane Tubing (PU)



Polyurethane's **3 specific materials** - ether, ester and food-grade "crystal" - offer excellent flexibility and outstanding use in a wide range of applications, allowing for up to **50% space reduction** when compared to semi-rigid PA tubing.

Fireproof PA Tubing



This **single-layer fireproof** tubing not only combines excellent resistance to pressure, temperature and flame, but also guarantees **non-toxic smoke** resulting from burn-off. This tubing eliminates the need for a stripping tool, thus preventing the risk of tube damage prior to connection.

Polyethylene Tubing (PE)



Parker Legris offers two types of polyethylene tubing: **"Advanced PE" 50% reticulated** and **Low Density PE**. Our range of "Advanced PE" tubing is designed for demanding environments, especially that of water treatment, without compromising operator **safety**.



Together, we can connect you to the best in technology. Better than ever before.

In this updated edition of the Parker Legris catalogue, we have developed the content, structure and layout to enable you to find the products and information you require as quickly as possible. 31 complementary ranges and more than 1000 additional part numbers have been included, widening the choice of solutions available in order to meet your requirements more effectively. By putting our knowledge and expertise at your fingertips, we strive to provide the day-to-day support you need when designing your industrial equipment.



aerospace
climate control
electromechanical
filtration
fluid & gas handling
hydraulics
pneumatics
process control
sealing & shielding



ENGINEERING YOUR SUCCESS.

www.parkerlegris.com

Parker Worldwide

Europe, Middle East, Africa

AE – United Arab Emirates, Dubai
Tel: +971 4 8127100
parker.me@parker.com

AT – Austria, Wiener Neustadt
Tel: +43 (0)2622 23501-0
parker.austria@parker.com

AT – Eastern Europe, Wiener Neustadt
Tel: +43 (0)2622 23501 900
parker.easteurope@parker.com

AZ – Azerbaijan, Baku
Tel: +994 50 2233 458
parker.azerbaijan@parker.com

BE/LU – Belgium, Nivelles
Tel: +32 (0)67 280 900
parker.belgium@parker.com

BG – Bulgaria, Sofia
Tel: +359 2 980 1344
parker.bulgaria@parker.com

BY – Belarus, Minsk
Tel: +375 17 209 9399
parker.belarus@parker.com

CH – Switzerland, Etoy
Tel: +41 (0)21 821 87 00
parker.switzerland@parker.com

CZ – Czech Republic, Klecany
Tel: +420 284 083 111
parker.czechrepublic@parker.com

DE – Germany, Kaarst
Tel: +49 (0)2131 4016 0
parker.germany@parker.com

DK – Denmark, Ballerup
Tel: +45 43 56 04 00
parker.denmark@parker.com

ES – Spain, Madrid
Tel: +34 902 330 001
parker.spain@parker.com

FI – Finland, Vantaa
Tel: +358 (0)20 753 2500
parker.finland@parker.com

FR – France, Contamine s/Arve
Tel: +33 (0)4 50 25 80 25
parker.france@parker.com

GR – Greece, Athens
Tel: +30 210 933 6450
parker.greece@parker.com

HU – Hungary, Budaörs
Tel: +36 23 885 470
parker.hungary@parker.com

IE – Ireland, Dublin
Tel: +353 (0)1 466 6370
parker.ireland@parker.com

IT – Italy, Corsico (MI)
Tel: +39 02 45 19 21
parker.italy@parker.com

KZ – Kazakhstan, Almaty
Tel: +7 7273 561 000
parker.easteurope@parker.com

NL – The Netherlands, Oldenzaal
Tel: +31 (0)541 585 000
parker.nl@parker.com

NO – Norway, Asker
Tel: +47 66 75 34 00
parker.norway@parker.com

PL – Poland, Warsaw
Tel: +48 (0)22 573 24 00
parker.poland@parker.com

PT – Portugal, Leca da Palmeira
Tel: +351 22 999 7360
parker.portugal@parker.com

RO – Romania, Bucharest
Tel: +40 21 252 1382
parker.romania@parker.com

RU – Russia, Moscow
Tel: +7 495 645-2156
parker.russia@parker.com

SE – Sweden, Spånga
Tel: +46 (0)8 59 79 50 00
parker.sweden@parker.com

SK – Slovakia, Banská Bystrica
Tel: +421 484 162 252
parker.slovakia@parker.com

SL – Slovenia, Novo Mesto
Tel: +386 7 337 6650
parker.slovenia@parker.com

TR – Turkey, Istanbul
Tel: +90 216 4997081
parker.turkey@parker.com

UA – Ukraine, Kiev
Tel: +380 44 494 2731
parker.ukraine@parker.com

UK – United Kingdom, Warwick
Tel: +44 (0)1926 317 878
parker.uk@parker.com

ZA – South Africa, Kempton Park
Tel: +27 (0)11 961 0700
parker.southafrica@parker.com

North America

CA – Canada, Milton, Ontario
Tel: +1 905 693 3000

US – USA, Cleveland
Tel: +1 216 896 3000

Asia Pacific

AU – Australia, Castle Hill
Tel: +61 (0)2-9634 7777

CN – China, Shanghai
Tel: +86 21 2899 5000

HK – Hong Kong
Tel: +852 2428 8008

IN – India, Gurgaon
Tel: +91 124 459 0600
legris.india@parker.com

JP – Japan, Tokyo
Tel: +81 (0)3 6408 3901

KR – South Korea, Seoul
Tel: +82 2 559 0400

MY – Malaysia, Shah Alam
Tel: +60 3 7849 0800

NZ – New Zealand, Mt Wellington
Tel: +64 9 574 1744

SG – Singapore
Tel: +65 6887 6300

TH – Thailand, Bangkok
Tel: +662 186 7000-99

TW – Taiwan, Taipei
Tel: +886 2 2298 8987

South America

AR – Argentina, Buenos Aires
Tel: +54 3327 44 4129

BR – Brazil, Sao Jose dos Campos
Tel: +55 800 727 5374

CL – Chile, Santiago
Tel: +56 2 623 1216

MX – Mexico, Apodaca
Tel: +52 81 8156 6000

European Product Information Centre

Free phone: 00 800 27 27 5374

(from AT, BE, CH, CZ, DE, DK, EE, ES, FI, FR, IE, IL, IS, IT, LU, MT, NL, NO, PL, PT, RU, SE, SK, UK, ZA)

