Screw pumps - PDA series with bell housing


For hydraulic oils, lubricating oils Admissible delivery pressure 10 bar Standard valve setting 6 bar

UNIFIED

Main field of application:

Low pressure lubrication systems, auxiliary filtration systems, cooling systems

Section and components



Functional characteristics standard version

Delivery flow	21 to 160 l/min (5,5 to 42,2 USGPN	<i>Λ</i>)						
Admissible delivery pressure*	up to 10 bar (145 psi)							
Admissible suction pressure	-0,4 to 2 bar (-5,8 to 29 psi)	For different values contact SEIM						
Kinematics viscosity	20 to 400 cSt	For different values contact SEIM						
Admissible temperature	0 to 100 °C (32 to 212 °F)	For different values contact SEIM						
Driving speed	750 to 3600 rpm							
Average noise level	56 ÷ 62 dB(A) at 2900 rpm according	56 ÷ 62 dB(A) at 2900 rpm according to pump dimension						
Recommended filtration	60 micron max, suction side (not abrasive contaminant)							
	ISO4406 19 / 16 - NAS 10							
Direction of rotation	clockwise, as seen from the driving s	side						


Reduced pressure limits apply due to fluid viscosity and driving speed
Consult the performance charts for the individual pump size
For different functional characteristics, please contact our sales department

Screw pumps - PDA series with bell housing

For hydraulic oils, lubricating oils Admissible delivery pressure 10 bar Standard valve setting 6 bar







Dimensional chart (mm)

MODELLO	Α	В	С	D	F	G	G1	Н	I	L	d2	d3	d4	d6
PDA029#201 STD.	101	1"	1"	67	353	127	226	44		122	130	165	200	
PDA032#201 STD.	191									122				
PDA040#201 STD.	191	11/4"	11/4"	67	374	127	247	48	35	140	130	165	200	M10
PDA029#201 OPT.	122	1"	1"	2	284	58	226	44		400	100	165	200	
PDA032#201 OPT.										122	130			
PDA040#201 OPT.	122	1¼"	1¼"	2	305	58	247	48		140	130	165	200	

<u>SEIM srl</u> Via A. Volta 17

20090 Cusago (MI) ITALY Tel. (+39) 02.90.39.21.1

Fax (+39) 02.90.39.21.41 e-mail: seim@seim.it

www.seim.it